



Brass Model UA

Venturi Balancing Data: Flow (gpm) versus
Differential Pressure (in W. C.)

Form No.: F234.1

Date: 8.06

Supersedes: F234.0 12.02

Using the Differential Pressure (D.P.) Tables

1. **The recommended ranges are shown in bold.**
2. Generally, the recommended low ΔP signal is 24" so it can be read on most instruments.
3. The upper limit is an effort to minimize the permanent pressure drop. However, any model can be operated above the limit if the permanent drop is acceptable.
4. The following equation has been approximated from the differential pressure table: $INWC = (B \cdot gpm)^2$
5. The permanent pressure loss can be calculated in the standard way from the valve's CV and flow rate: $PSID = (gpm/CV)^2$

Venturi No.	B	C _v
1	24.4	0.283
2	11.1	0.771
3	4.86	2.15
4	2.21	4.79
5	1.78	5.95
6	0.819	17.5
7	0.467	18.4
8	0.217	68.5

Differential Pressure: Inches W.C.

Flow Rate (gpm)	1	2	3	4	5	6	7	8
0.1	7.3							
0.2	27.1	5.5						
0.3	58.6	12.1						
0.4	101.2	21.2						
0.5	154.7	32.7	6.7					
0.6	218.8	46.7	9.5					
0.65	254.7	54.6	11.1					
0.7	293.3	63.1	12.8					
0.8	378.0	81.9	16.6					
0.9	472.8	103.1	20.9					
0.95	524.0	114.6	23.2					
1.0		126.7	25.6					
1.1		152.6	30.8	5.4				
1.2		180.9	36.5	6.5	5.1			
1.3		211.5	42.6	7.6	6.0			
1.4		244.4	49.1	8.9	6.9			
1.5		279.6	56.2	10.2	7.9			
1.6		317.2	63.6	11.6	9.0			
1.7		357.1	71.6	13.2	10.1			
1.8		399.2	79.9	14.8	11.3			
1.9		443.7	88.7	16.5	12.6			
2.0		490.4	98.0	18.4	13.9			
2.2			117.9	22.3	16.7			
2.4			139.5	26.7	19.8			
2.6			162.8	31.4	23.2	5.0		
2.8			188.0	36.6	26.8	5.8		
3.0			214.8	42.1	30.7	6.7		
3.2			243.4	48.0	34.8	7.6		
3.4			273.7	54.4	39.2	8.5		
3.6			305.7	61.1	43.9	9.5		
3.8			339.4	68.2	48.7	10.6		
4.0			374.8	75.8	53.9	11.7		
4.2			412.0	83.7	59.3	12.8	5.3	
4.4			450.8	92.1	64.9	14.1	5.7	
4.6			491.3	100.9	70.8	15.3	6.2	
4.8			533.5	110.0	77.0	16.7	6.7	
5.0				119.6	83.4	18.0	7.3	
5.2				129.6	90.1	19.5	7.8	
5.4				140.0	97.0	21.0	8.4	
5.6				150.8	104.1	22.5	9.0	
5.8				162.0	111.5	24.1	9.6	
6.0				173.6	119.2	25.7	10.2	
6.2				185.7	127.1	27.4	10.8	
6.4				198.1	135.2	29.2	11.5	
6.6				211.0	143.6	31.0	12.2	
6.8				224.2	152.2	32.9	12.9	
7.0				237.9	161.1	34.8	13.6	
7.5				274.0	184.4	39.8	15.4	

Differential Pressure: Inches W.C. (cont.)

Flow Rate (gpm)	1	2	3	4	5	6	7	8
8.0				312.6	209.2	45.1	17.4	
8.5				353.8	235.6	50.8	19.5	
9.0				397.7	263.5	56.8	21.6	
9.5				444.2	292.9	63.1	23.9	
10.0				493.3	323.8	69.7	26.3	5.1
11.0					390.2	83.9	31.4	6.2
12.0					462.7	99.4	36.9	7.3
13.0					541.1	116.2	42.8	8.6
14.0						134.3	49.2	9.9
15.0						153.6	55.9	11.4
16.0						174.2	63.0	12.9
17.0						196.0	70.5	14.5
18.0						219.2	78.4	16.2
19.0						243.5	86.7	18.0
20.0						269.1	95.3	20.0
21.0						296.0	104.4	22.0
22.0						324.1	113.8	24.1
23.0						353.4	123.6	26.3
24.0						384.0	133.7	28.5
25.0						415.8	144.3	30.9
26.0						448.8	155.2	33.4
27.0						483.1	166.4	36.0
28.0						518.5	178.1	38.6
29.0							190.1	41.4
30.0							202.4	44.2
31.0							215.1	47.1
32.0							228.2	50.2
33.0							241.6	53.3
34.0							255.3	56.5
35.0							269.5	59.8
36.0							283.9	63.2
37.0							298.7	66.7
38.0							313.9	70.3
39.0							329.4	74.0
40.0							345.3	77.7
41.0							361.5	81.6
42.0							378.0	85.5
43.0							394.9	89.6
44.0							412.1	93.7
45.0							429.7	97.9
46.0							447.6	102.3
47.0							465.8	106.7
48.0							484.4	111.2
49.0							503.3	115.7
50.0								120.4
52.0								130.0
54.0								140.0
56.0								150.4
58.0								161.1
60.0								172.2
62.0								183.6
64.0								195.4
66.0								207.6
68.0								220.1
70.0								233.0
72.0								246.2
74.0								259.8
76.0								273.8
78.0								288.1
80.0								302.7
82.0								317.8
84.0								333.1
86.0								348.9
88.0								365.0
90.0								381.4
92.0								398.2
94.0								415.4
96.0								432.9
98.0								450.8
100.0								469.0
102.0								487.6
104.0								506.5