



Model UB
 Ball valve used on
 hose kit at left

Model UB shown with optional Pressure / Temperature ports.

Product Information

Kit C includes a Model UB ball valve, Model YC strainer with ball valve and two Model S2/S3 hose assemblies.

Model UB is a shut-off valve with large diameter plated ball and Teflon seats. Stem is blowout proof with EPDM O-ring and Teflon packing with packing nut. Ball valve end available thread or sweat – please specify.

strainer is removable from the valve body for inspection and cleaning without breaking the main piping.

Model YC is a combination ball valve, y-strainer and union with seven (7) accessory port locations. 20 mesh stainless steel

S2/S3 hose assembly has a braided stainless steel outer band with CPE/EPDM inner tube and brass or steel fittings.

Dimensions not to be used for construction unless prints certified by factory.

Dimensions

Kit Size	Overall Length – 2 Ft. Kit	
	Return	Supply
1/2"	31"	31"
3/4"	32"	32"
1"	34"	34"
1 1/4"	34"	34"
1 1/2"	35"	35"
2"	37"	37"

Notes

Overall length of kit may vary by ± 1" and is provided only as an estimate.

All hoses are stainless steel braided and rated 300 psig maximum working pressure.

Each kit is shipped hand tight unless otherwise stated (see connection charges in F132, VersaFlow Price Guide).

Bend Radius Specifications

Hose I.D.	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
Minimum Bend Radius	5"	7"	7"	8"	9"	10"

Never use a bending radius less than the minimum amount shown above.

Options Available

- AA** Automatic Air Vent
- AV** Manual Air Vent
- EH** Extended Handle
- HN** Hose End Drain Valve with Cap

- MH** Micro Handle
- MS** Memory Stop
- PI** Plastic ID Tag
- PL** Plug

- PT** Pressure/Temperature Test Ports
- SE** Stem Extender
- XL** Extended Pressure/Temperature Test Ports

Various convenience fittings are available.